









# Wall Feed-through

## Types and Features — Selection Table

	Description	ID number	Type
	<ul style="list-style-type: none"> <li>■ M12 × 1 wall feed-through, 4-pin</li> <li>■ Material: Stainless steel</li> <li>■ Male on female</li> <li>■ Voltage: 150 V</li> <li>■ Current load: 4 A</li> <li>■ Temperature: -40 °C...+80 °C</li> <li>■ IEC IP68; NEMA 1, 3, 4, 6P</li> <li>■ Approval: UL, CSA</li> </ul>	6939625	FKV-FSV4.4/M12
	<ul style="list-style-type: none"> <li>■ M12 × 1 wall feed-through, 4-pin</li> <li>■ Male on female</li> <li>■ Voltage: 150 V</li> <li>■ Current load: 4 A</li> <li>■ Temperature: -40 °C...+80 °C</li> <li>■ IEC IP68; NEMA 1, 3, 4, 6P</li> <li>■ Approval: UL, CSA</li> </ul>	6922806	FK-FS4.4/M12
	<ul style="list-style-type: none"> <li>■ M12 × 1 wall feed-through, 5-pin</li> <li>■ Male on female</li> <li>■ Voltage: 150 V</li> <li>■ Current load: 4 A</li> <li>■ Temperature range: -40 °C...+80 °C</li> <li>■ IEC IP68; NEMA 1, 3, 4, 6P</li> <li>■ Approval: UL, CSA</li> </ul>	6922807	FK-FS4.5/M12
	<ul style="list-style-type: none"> <li>■ M12 × 1 wall feed-through, 8-pin</li> <li>■ Male on female</li> <li>■ Voltage: 36 V</li> <li>■ Current load: 1.5 A</li> <li>■ Temperature: -40 °C...+80 °C</li> <li>■ IEC IP68; NEMA 1, 3, 4, 6P</li> <li>■ Approval: UL, CSA</li> </ul>	6922808	FK-FS8/M12
	<ul style="list-style-type: none"> <li>■ 7/8" wall feed-through, 3-pin</li> <li>■ Male on female</li> <li>■ Voltage: 600 V</li> <li>■ Current load: 10 A</li> <li>■ Temperature: -40...+105°C</li> <li>■ IEC IP67; NEMA 1, 3, 4</li> </ul>	6604206	RSF-RKF30/22
	<ul style="list-style-type: none"> <li>■ 7/8" wall feed-through, 4-pin</li> <li>■ Male on female</li> <li>■ Voltage: 600 V</li> <li>■ Current load: 9 A</li> <li>■ Temperature: -40 °C...+105°C</li> <li>■ IEC IP67; NEMA 1, 3, 4</li> </ul>	6915014	RSF-RKF40/22
	<ul style="list-style-type: none"> <li>■ 7/8" wall feed-through, 5-pin</li> <li>■ Male on female</li> <li>■ Voltage: 600 V</li> <li>■ Current load: 9 A</li> <li>■ Temperature: -40 °C...+105°C</li> <li>■ IEC IP67; NEMA 1, 3, 4</li> </ul>	6914891	RSF-RKF50/22









# Adapter

## Types and Features — Selection Table


	Description	ID number	Type
	<ul style="list-style-type: none"> <li>■ Robust, plastic-coated adapter</li> <li>■ M12 × 1 female - M12 × 1 male Ø 8 mm</li> <li>■ 3-pin</li> <li>■ Protection class IP67</li> <li>■ Voltage: 60 V</li> <li>■ Current load: 4 A</li> <li>■ Temperature: -30 °C...+90 °C</li> </ul>	8008083	FKM3-ESP3S
	<ul style="list-style-type: none"> <li>■ Robust, plastic-coated adapter</li> <li>■ M12 × 1 female - M12 × 1 male Ø 8 mm</li> <li>■ 4-pin</li> <li>■ Protection class IP67</li> <li>■ Voltage: 30 V</li> <li>■ Current load: 4 A</li> <li>■ Temperature: -30 °C...+90 °C</li> </ul>	8008084	FKM4-ESP4S
	<ul style="list-style-type: none"> <li>■ Robust, plastic-coated adapter</li> <li>■ M12 × 1 male - M8 × 1 female</li> <li>■ 3-pin</li> <li>■ Protection class IP67</li> <li>■ Voltage: 60 V</li> <li>■ Current load: 4 A</li> <li>■ Temperature: -30 °C...+90 °C</li> </ul>	8008079	FSM3-SKP3
	<ul style="list-style-type: none"> <li>■ Robust, plastic-coated adapter</li> <li>■ M12 × 1 male - M8 × 1 female</li> <li>■ 3-pin</li> <li>■ Protection class IP67</li> <li>■ Voltage: 30 V</li> <li>■ Current load: 4 A</li> <li>■ Temperature: -30 °C...+90 °C</li> </ul>	8008138	FSM4-SKP4

# Closure Cap

## Types and Features — Selection Table

	Description	ID number	Type
	<ul style="list-style-type: none"> <li>■ Closure caps for <math>\varnothing</math> 8mm snap, black</li> <li>■ Protection class: IP67 (installed)</li> <li>■ 100 pcs. per bag</li> </ul>	8010971	SCHUTZSTOPFEN 8MM SNAP. SCHWARZ
	<ul style="list-style-type: none"> <li>■ Closure cap for M8 <math>\times</math> 1 female connectors</li> <li>■ No internal wiring</li> <li>■ Nylon, black</li> <li>■ Protection class: IP67 (installed)</li> </ul>	6936046	Schutzstopfen ISK-M8
	<ul style="list-style-type: none"> <li>■ Closure cap for M12 <math>\times</math> 1 female connectors</li> <li>■ Material: Polyurethane, black</li> <li>■ Protection class: IP67 (installed)</li> </ul>	6936055	VS-M12-BK
	<ul style="list-style-type: none"> <li>■ Closure cap for M12 <math>\times</math> 1 female connectors</li> <li>■ Material: Polyurethane, yellow</li> <li>■ Protection class: IP67 (installed)</li> <li>■ 100 pcs. per bag</li> </ul>	6999003	VS-M12-YE
	<ul style="list-style-type: none"> <li>■ Closure caps for M12 <math>\times</math> 1 connector</li> <li>■ Material: Polyurethane, yellow</li> <li>■ Protection class: IP67 (installed)</li> <li>■ 100 pcs. per bag</li> </ul>	6999025	VK-M12 (100 pcs)VERSCHLUSSKAPPE
	<ul style="list-style-type: none"> <li>■ Closure cap for 7/8" female connectors</li> <li>■ Nickel plated brass, black</li> <li>■ With stainless steel chain, 150 mm</li> </ul>	6914829	RSM-CC
	<ul style="list-style-type: none"> <li>■ Closure cap for 7/8" male connector</li> <li>■ Nickel plated brass, black</li> <li>■ With stainless steel chain, 150 mm</li> </ul>	6914831	RKM-CC

Types and Features — Selection Table



Description

ID number

Type





- Closure cap for 7/8" female connectors
- Material: polyamide, black
- Protection class: IP67 (installed)

6936051

VZ8

# Fastening nut and labels

## Types and Features — Selection Table

	Description	ID number	Type
	<ul style="list-style-type: none"> <li>■ Material: Metal, CuZn, nickel-plated</li> <li>■ Screw-in thread: M16 × 1.5</li> <li>■ Wrench size: SW17</li> <li>■ Height: 6mm</li> </ul>	6936166	SECHSKANTMUTTER M16X1.5. SW17
	<ul style="list-style-type: none"> <li>■ Material: Metal, CuZn, nickel-plated</li> <li>■ Screw-in thread: M16 × 1.5</li> <li>■ Wrench size: SW19</li> <li>■ Height: 3mm</li> </ul>	6936389	SECHSKANTMUTTER M16X1.5. SW19
	<ul style="list-style-type: none"> <li>■ Material: Polycarbonate (PC)</li> <li>■ Color: white, similar to RAL 9016</li> <li>■ Label length: 18 mm</li> <li>■ Label height: 4 mm</li> <li>■ Halogen-free</li> <li>■ Flame-retardant (fire class V0)</li> <li>■ Temperature range: -40 °C...+140 °C</li> <li>■ RoHS-compliant</li> <li>■ Single line labeling (labeling technology: Plotter, laser, ink jet, waterproof pen)</li> </ul>	6936206	BLANK-LABEL-FOR-CORD-SETS-TEL-TXL